

SPECIFICATIONS

G Australia

			SoniQ i	_
Model			S4412	
Printing Technology			Drop-on-demand, Piezo electric inkjet	
Print Heads			Industrial Grade Jetting Assemblies	
Media	Width		3300 mm (129 in)	
	Thickness		Maximum 3.0 mm (120 mil) with Liner (flexible)	
	Roll Outer Diameter		Maximum 300 mm (12 in), 50.8 (2 in)	
	Roll Weight		Maximum 90 kg	
	Core Diameter		76.2 mm (3 in)	
	Types		SAV, PAV Banner, Backlit Film, Window Film, Fabric (For Solvent Printing)	
Printing Width			Maximum 3200 mm (126 in)	
Ink	Туре		Solvent / Mid Solvent Inks	
	No. of Colors		4 Colors (CMYK)	
Printing Resolution (dots per inch)			Maximum up to 1440 dpi	
Distance Accuracy		Error of less than $\pm0.3\%$ of distance travelled, or ±0.3 mm whichever is great		
Media Heating System			Pre-heater and post-heater , setting range for the pre-set temperature: 30°C to 60°C Dryer setting range for the pre-set temperature: 30°C to 60°C	
Connectivity			High Speed USB	
Power Requirements (Peak)			AC 220 v ±10%, 20 Amps, 50/60 Hz	
Printer Dimensions			4525mm x 885mm x 1500mm (LxWxH)	
RIP Software			FlexiPrint	
Weight (approx. with stand)			642 Kgs	
Environmental	Power ON		Temperature: 18°C to 28°C Humidity: 20 to 40% RH (non-condensing)	
	Power OFF		Temperature: 5 to 40°C Humidity: 20 to 80%RH (non-condensing)	
Speed (In Sqm/hr)	Print DPI	Passes	Sqm/hr	Sqft/hr
Mode 1	360 x 360	2	114	1232
Mode 2	360 x 540	3	77	830
Mode 3	360 x 720	4	62	664
Mode 4	720 x 720	4	33	348
Wode 4				
Mode 5	720 x 1080	6	22	232

Note: Take up roller option also provided

COLORJET GROUP


INDIA: B-195, Phase-II, Noida-201305 (U.P.), INDIA. T +91 120 4548195 | **DUBAI:** Block-A, Office No: 115, Hamsah Building, Karama, P.O. Box: 123360, Dubai-UAE. T 00971 43961744 | **sales@colorjetgroup.com** | **www.colorjetgroup.com**


Accessories shown along with different printers in this brochure are not part of standard equipment. Color may vary from actual body color due to printing on paper. Colorjet reserves the right to change specifications without prior notice. All speed limits mentioned in this brochure were tested under special conditions. All trademarks, logos, symbols and designs depicted / mentioned in this brochure are trade names, trademarks and copyrights of their respective brand owners.



ROBUST FUTURISTIC PRINTER WITH UNMATCHABLE POWER AND SPEED













SONIQI 3.2 MTR Roll-to-Roll Printer

INTENSIFY
SIGNAGE PRINTING
EXPERIENCE WITH
ULTRA-MODERN SONIQ İ


The span-new **SoniQi** is an ideal choice for the indoor and outdoor signage industry. Blend with splendid features; the machine delivers excellent print quality at an ultra-fast speed of **1232 sqft/hr.** It offers maximum performance at a minimum investment and develops business potential. With **3.2 mtr roll** capability to accommodate every media size, it can consistently produce precise and vibrant prints.

The heavy-duty forefront industrial print heads of the machine are engineered for lasting performance. It is an excellent alternative for huge savings on inks & time with pressure purge for individual colors.




PREMIUM FEATURES:






SoniQi comes with unmatched FGP technology, which ensures extremely less deviation between jet to bed distance(<**0.1mm**) over the entire printing span and maintains consistent print quality.






Enhance printing Precision on the Border of the Media and helps in the smooth change over of carriage direction, leading to less jerk and lesser wear and tear.





Optimized with digital observation of **Ink viscosity curve**, which helps in maintaining a stable waveform of jetting and ensures constant print quality.




SoniQi offers a fifth button for **declogging**, which helps in maintaining pressure for efficient cleaning and reducing ink wastage













WORK STATION E



Hoarding, Outdoor Banner, Backlit Hoardings, Dropdown Banner, Floor Standee, Backlit Display, Vehicle Wraps and Many More..



MAX RESOLUTION 1440 dpi SUPER POWER DRYER



The super-fast innovation

